

Pastel-colored Lipstick

Makeup | FM-MK-2025019

Features

Moisturizes lips, locks in hydration, and protects the lip skin barrier.

Ingredients

● Synfumei® Synthetic Wax 6602, ● Cerafumei® Sunflower Wax 5301, ● CireEster BW1822 and ● Microfumei® Microcrystalline Wax 6302 are combined to provide desirable stability, hardness, texture and pay-off property.

Phase	Ingredients	INCI	% wt	Function
A	Synfumei® Synthetic Wax 6602 ¹	Synthetic Wax	7.00	Structuring agent
	Cerafumei® Sunflower Wax 5301 ¹	Helianthus Annuus (Sunflower) Seed Wax	4.00	Structuring agent
	CireEster BW 1822 ¹	Stearyl Alcohol Beewax Ester (and) Arachidyl Alcohol Beewax Ester	2.00	Structuring agent
	Microfumei® Microcrystalline Wax 6302 ¹	Microcrystalline Wax	1.00	Structuring agent
	COSMOL 43V ²	Polyglyceryl-2Triisostearate	26.00	Dispersant
	COSMOL 222 ²	Diisostearyl Malate	31.00	Emollient
	Salacos 5408 ²	Pentaerythritol Tetrakis (Ethylhexanoate)	6.00	Emollient
	Eviol DG 11 ³	Caprylic/Capric Triglyceride	7.00	Emollient
	PANALANE® H-300E ⁴	Hydrogenated Polyisobutene	9.00	Skin conditioner
	LIPEX Shea ⁵	Butyrospermum Parkii (Shea) Butter	1.00	Emollient
DW Jojoba Colorless ⁴	Simmondsia Chinensis (Jojoba) Seed Oil	1.00	Emollient	
Lipovol MAC-Ternifolia ⁴	Macadamia Ternifolia Seed Oil	1.00	Emollient	
Vitamin E-Acetate ⁶	Tocopheryl Acetate	0.50	Antioxidant	
euxyl® PE 9010 ⁷	Phenoxyethanol (and) Ethylhexylglycerin	0.20	Preservative	
B	Silica Bead SB-300 ⁵	Silica	1.00	Skin conditioner
	Covenol Red OS 3707 ⁸	CI 15850 (and) Octyldodecanol (and) Stearic Acid (and) Magnesium Hydroxide (and) Aluminum Hydroxide (and) Polyhydroxystearic Acid	0.40	Colorant
	Covenol Yellow OS 1705 ⁸	CI 19140 (and) Octyldodecanol (and) Stearic Acid (and) Magnesium Hydroxide (and) Aluminum Hydroxide (and) Polyhydroxystearic Acid	1.40	Colorant
	Covenol Red OS 3701 ⁸	CI 15180 (and) Octyldodecanol (and) Stearic Acid (and) Magnesium Hydroxide (and) Aluminum Hydroxide (and) Polyhydroxystearic Acid	0.50	Colorant

Procedure:

- Add Phase A into the main tank, and heat to 85–90°C until fully melted.
- Cool down to 50–60°C, add Phase B and homogenize at 3000 rpm for 10 min until uniformly dispersed.
- Degas before filling.

Specification:

Appearance: Stick texture
Break off value: 631.5g (test equipment: CT3 texture analyzer, test condition: probe: TA44, target value: 10.0mm, contact load: 2.5g, test speed: 1.0mm/s.)
Cutting value: 239.3g (test equipment: CT3 texture analyzer, test condition: probe: TA53, target value: 12.0mm, contact load: 5.0g, test speed: 1.0mm/s.)

Stability:

Pass 1 month at -18°C, 5°C, 25°C, 30°C, 45°C and 50°C.
Freeze-Thaw test: 3 cycles.



Suppliers: 1: Fumei 2: Nisshin OilliO 3: Eyvap oleo 4: Vantage 5: Miyoshi Kasei Inc. 6: BASF 7: Ashland 8: Sensient

Disclaimer:

The information in this publication is believed to be accurate and is given in good faith, but no representation or warranty as to its completeness or accuracy is made. Suggestions for uses or applications are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR THAT DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without the permission of the patent owner.