

Lip Scrub

Makeup | FM-MK-2025020

Features

Gently exfoliates to revitalize skin, while a blend of natural oils delivers long-lasting moisture and nourishing comfort.

Ingredients

🐝 Cerafumei® White Beeswax 2002 and 🕯 Cerafumei® Candelilla Wax 5501 act as structuring agents and thickeners to provide desirable texture, stability and pay-off property.

● Sensgel® VP 6801H: a vegetable-derived emollient with a soft and silky texture. It offers excellent spreadability while providing both moisturizing and occlusive properties.

Phase	Ingredients	INCI	% wt	Function
A	Cerafumei® White Beeswax 2002 ¹	Beeswax	10.00	Structuring agent
	Cerafumei® Candelilla Wax 5501 ¹	Euphorbia Cerifera (Candelilla) Wax	8.00	Structuring agent
	Sensgel® VP 6801H ¹	Ricinus Communis (Castor) Seed Oil (and) Rhus Succedanea Fruit Wax (and) Ascorbyl Palmitate (and) Tocopherol (and) Helianthus Annuus (Sunflower) Seed Oil	10.00	Emollient
	COSMOL 222 ²	Diisostearyl Malate	9.80	Emollient
	COSMOL 43V ²	Polyglyceryl-2Triisostearate	6.00	Dispersant
	Lipovol MAC-Ternifolia ³	Macadamia Ternifolia Seed Oil	6.00	Emollient
	NIKKOL Olive Oil ⁴	Olea Europaea (Olive) Fruit Oil	6.00	Emollient
	COYI CEH ⁵	Cetyl Ethylhexanoate	4.50	Emollient
	Meadowfoam Oil ⁶	Limnanthes Alba (Meadowfoam) Seed Oil	4.00	Emollient
	BV80-Refined High Oleic ⁷	Helianthus Annuus (Sunflower) Seed Oil	4.00	Emollient
	Sunflower Oil			
	Squalane ³	Squalane	1.00	Emollient
	Vitamin E-Acetate ⁸	Tocopheryl Acetate	0.50	Antioxidant
euxyl® PE 9010 ⁹	Phenoxyethanol (and) Ethylhexylglycerin	0.20	Preservative	
B	Sucrose ¹⁰	Sucrose	30.00	Skin conditioner

Suppliers: 1: Fumei 2: Nisshin Oillio 3: Vantage 4: Nikkol 5: COYI 6: Elementis 7: Cargill 8: BASF 9: Ashland 10: Nestle

Procedure:

- Add Phase A into the main tank, and heat to 80–85°C until fully melted.
- Degas, cool down to 40–45°C, then add Phase B and mix until uniform.

Specification:

Appearance: Paste texture
Hardness: 147.8g (test equipment: CT3 texture analyzer, test condition: probe: TA44, target value: 5.0mm, contact load: 2.5g, test speed: 1.0mm/s.)

Stability:

Pass 1 month at -18°C, 5°C, 25°C, 30°C, 45°C and 50°C.
Freeze-Thaw test: 3 cycles.



Disclaimer:

The information in this publication is believed to be accurate and is given in good faith, but no representation or warranty as to its completeness or accuracy is made. Suggestions for uses or applications are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR THAT DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without the permission of the patent owner.